

PRODUCT SPECIFICATIONS

WHEELED BATTERY CHARGERS

Part Number	Continuous Amperage Charging Rate	Re-Flash Power Supply Output Amperage	Crank Assist	Operating Charging Voltage	Battery Types	Indoor / Outdoor Rated	Smart Charger / Battery Diagnostics	Adjustable Charging Voltage	Adjustable Charging Amperage	Adjustable Re-Flash Power Supply Voltage	Polarity Indicated and/or Protected	Memory Saver Mode	DC Cable Length and Gauge	Clamp Rating	A/C Cord Length	Weight (Pounds) Lbs	Dimensions (LxWxH)	Warranty Code	COO	Page Number
6001A	100/75A	N/A	375A	6/12V	4	Y	N	N	N	N	Y	N	8' 4AWG	500A	10' 14-3	58	17.25x16.5x30"	1	US ⁹	8
6002B	100/80A	N/A	400A	6/12/18/24	4	Y	N	N	N	N	Y	N	8' 4AWG	500A	10' 14-3	70	17.25x16.5x30"	1	US ⁹	8
6006AGM	70/65/30A	N/A	280A	6/12/24V	5	Y	N	N	N	N	N	N	7' 4AWG	500A	6-1/2' 16-3	53	17.25x16.5x26.5"	1	US ⁹	9
6009AGM	70/60/2A	N/A	265A	6/12V	5	Y	N	N	N	N	Y	N	7' 4AWG	500A	6-1/2' 16-3	48	17.25x16.5x26.5"	1	US ⁹	9
6012AGM	70/60A	N/A	250A	6/12V	5	Y	N	N	N	N	N	N	6 1/2' 6 1/2AWG	400A	6-1/2' 16-3	48	17.25x16.5x26.5"	1	US ⁹	9
6023	60/50/25A	N/A	300A	6/12/24V	4	Y	N	N	N	N	N	N	8' 4AWG	400A	8' 230VAC	50	15.5x19x21.5"	10	US ⁹	36
6027B	90/75/55A	N/A	500A	6/12/24V	4	Y	N	N	N	N	Y	N	8' 4AWG	500A	8' 230VAC	75	15.5x19x21.5"	10	US ⁹	36
6508A/6508X	60A	70A	270A	12V	6	Y	Y	N	N	N	Y	N	6 1/2' 16-3AWG	300A	6' 18-3 220V	49	17.25x16.5x26.5"	10	US ⁹	37
6512/6512G	100/80/30A	N/A	500A	6/12/24V	4	Y	N	N	N	N	N	N	6 1/2' 4AWG	400A	8' 230VAC	49	15.5x19x21.5"	10	US ⁹	36
ESS6007B	40A	45A	130A	12V	6	Y	Y	N	N	N	Y	N	6 1/2' 6 1/2AWG	400A	6' 18-3	47	17.25x16.5x26.5"	2	US ⁹	4
ESS6008	60A	70A	270A	12V	6	Y	Y	N	N	N	Y	N	6 1/2' 4AWG	400A	6' 16-3	47	17.25x16.5x26.5"	2	US ⁹	4
ESS6008MSK	60A	70A	270A	12V	6	Y	Y	N	N	N	Y	Y	6 1/2' 4AWG	400A	6' 16-3	47	17.25x16.5x26.5"	2	US ⁹	4
ESS6011	70/35A	70A	270A	12/24V	6	Y	Y	N	N	N	Y	N	6 1/2' 4AWG	500A	6' 16-3	49	17.25x16.5x26.5"	2	US ⁹	5
MIL6011	70/35A	70A	270A	12/24V	6	Y	Y	N	N	N	Y	N	6 1/2' 4AWG NATO 13' 4AWG	500A	6' 16-3	49	17.25x16.5x26.5"	2	US ⁹	5
IBC6008	60A	70A	270A	12V	7	Y	Y	Y	Y	Y	Y	N	6 1/2' 4AWG	400A	6' 16-3	47	17.25x16.5x26.5"	2	US ⁹	3
IBC6008MSK	60A	70A	270A	12V	7	Y	Y	Y	Y	Y	Y	Y	6 1/2' 4AWG	400A	6' 16-3	48	17.25x16.5x26.5"	2	US ⁹	3
US20	40/40/10A	N/A	200A	6/12V	4	Y	Y	N	N	N	N	N	6 1/2' 6 1/2AWG	400A	6' 16-3	35	13.5x15x24"	8	US ⁹	10

¹ Two Year Bumper to Bumper and 5 Year on Transformer and Rectifier
² Two Year Bumper to Bumper and 3 Year on Transformer and Rectifier
³ One Year Bumper to Bumper
⁴ SLA
⁵ SLA, AGM
⁶ SLA, AGM, Gel-Cell
⁷ SLA, AGM, EFB, Lithium-Ion, Gel-Cell
⁸ Two Year Bumper to Bumper
⁹ Made in the USA with US and Globally Sourced Parts.
¹⁰ Please call for warranty information.

BENCH TOP BATTERY CHARGERS

Part Number	Continuous Amperage Charging Rate	Re-Flash Power Supply Output Amperage	Crank Assist	Operating Charging Voltage	Battery Types	Indoor / Outdoor Rated	Smart Charger / Battery Diagnostics	Adjustable Charging Voltage	Adjustable Charging Amperage	Adjustable Re-Flash Power Supply Voltage	Polarity Indicated and/or Protected	Memory Saver Mode	DC Cable Length and Gauge	Clamp Rating	A/C Cord Length	Weight (Pounds) Lbs	Dimensions (LxWxH)	Warranty Code	COO	Page Number
6010B	60/60/30A	N/A	230A	6/12/24V	4	N/A	N	N	N	N	Y	N	7' 6 1/2AWG	500A	6-1/2' 16-3	38	17x16x17"	1	US ⁹	10
9002A	1.5A	N/A	N/A	12V	6	N/A	N	N	N	N	Y	N	15" 18AWG	50A	8' 18-2	1	8.5x7x1.5"	3	CN	16
9003A	1A	N/A	N/A	6/12V	6	N/A	N	N	N	N	Y	N	12' 18AWG	50A	10' 18-2	1	11.5x7x3"	3	CN	16
9004A	1.5A	N/A	N/A	12V	6	N/A	N	N	N	N	Y	N	4' 18-2AWG	50A	6' 18-3	1	10.5x8.5x3"	3	CN	16
9425	20A	20A	N/A	12V	6	N/A	Y	N	N	N	Y	N	6 1/2' 10AWG	300A	6' 18-3	21	14x11.5x11.5"	3	US ⁹	7
9525A/9525X	20A	20A	N/A	12V	6	N/A	Y	N	N	N	Y	N	6 1/2' 10AWG	300A	6' 18-3 240AC	21	14x11.5x11.5"	10	US ⁹	37
9640	40A	45A	N/A	12V	6	N/A	Y	N	N	N	Y	N	6 1/2' 6 1/2AWG	400A	6' 18-3	38	17x16x17"	3	US ⁹	7
3055A	10/2A	N/A	50A	6/12V	6	N/A	N	N	N	N	Y	N	6 1/2' 6 1/2AWG	75A	6' 16-3	14	10.5x10x5.5"	3	CN	15
3075A	12/2A	N/A	75A	6/12V	6	N/A	N	N	N	N	Y	N	6 1/2' 6 1/2AWG	75A	6' 16-3	15	10.5x10x5.5"	3	CN	15
3100A	15/2A	N/A	100A	6/12V	6	N/A	N	N	N	N	Y	N	6 1/2' 6 1/2AWG	75A	6' 16-3	18	10.5x10x5.5"	3	CN	15

¹ Two Year Bumper to Bumper and 5 Year on Transformer and Rectifier
² Two Year Bumper to Bumper and 3 Year on Transformer and Rectifier
³ One Year Bumper to Bumper
⁴ SLA
⁵ SLA, AGM
⁶ SLA, AGM, Gel-Cell
⁷ SLA, AGM, EFB, Lithium-Ion, Gel-Cell
⁸ Two Year Bumper to Bumper
⁹ Made in the USA with US and Globally Sourced Parts.
¹⁰ Please call for warranty information.

MULTI-BATTERY CHARGERS

Part Number	D.C. Output	A.C. Input	Charging Capacity	Battery Types	Parallel / Series / Individual Charger	Smart Charger / Battery Diagnostics	Charge Rate Settings	Volt Meter	Amp Meter	DC Cable Length and Gauge	Clamp Rating	A/C Cord Length	Weight (Pounds) Lbs	Dimensions (LxWxH)	Warranty Code	COO	Page Number
6065/6065S	30A, 14.9V	108-132V, 7.5A 60Hz	Up to 10 12V	7	P	N	16	11-17V	0-10A	6 1/2' 6 1/2AWG	N/A	6-1/2' 16-3	40	16x19x16"	3	US ⁹	19 37
6066A	60/30A, 14.9V	120V, 12A 60Hz	Up to 20 12V	5	P	Y	2	11-17V	0-100A	6 1/2' 6 1/2AWG	N/A	6-1/2' 16-3	40	16x19x16"	3	US ⁹	17
6068	110A, 15.5V	190-262V, 13.9A 50/60Hz	Up to 36 12V	7	P	N	16	0-19.99V	1-110A	5' 1 AWG	N/A	Permanent Installation Only	83	14x16x26"	3	US ⁹	19
6078	30A, 14.9V	230V, 50/60Hz	Up to 10 12V	7	P	N	16	11-17V	1-50A	8' 10/2 AWG	N/A	6-1/2' 14-3	40	16x19x16"	10	US ⁹	19
6080A	6A, 106V	120V, 8A 60Hz	1 to 36 Cells	7	S	N	64	N/A	0-6A	8' 10/2 AWG	300A	6-1/2' 16-3	40	16x19x16"	3	US ⁹	18
6082	6A, 0-158V	120V, 13A 60Hz	1 to 60 Cells	7	S	N	Adjustable	N/A	0-6A	8' 10/2 AWG	100A	6-1/2' 14-3	45	16x19x16"	3	US ⁹	18
6366	20A X 4 CH	120V, 12.5A 60Hz	1 to 4 12V	6	I	Y	Automatic	N/A	N/A	4 Sets 6' 12/2 AWG	300A	6-1/2' 16-3	40	16x19x16"	3	US ⁹	17

¹ Two Year Bumper to Bumper and 5 Year on Transformer and Rectifier
² Two Year Bumper to Bumper and 3 Year on Transformer and Rectifier
³ One Year Bumper to Bumper
⁴ SLA
⁵ SLA, AGM
⁶ SLA, AGM, Gel-Cell
⁷ SLA, AGM, EFB, Lithium-Ion, Gel-Cell
⁸ Two Year Bumper to Bumper
⁹ Made in the USA with US and Globally Sourced Parts.
¹⁰ Please call for warranty information.